

Product data sheet

Specifications



Expansion Pod, NetBotz, Rack Mount, 175 Rack Access, TAA [TAA]

NBPD0150TAA

Overview

Presentation	Sensor pod optimized for rack mounting that supports 6 Universal Sensors.
Lead time	Usually in Stock

Main

Product or Component Type	Rack enclosure
Range of Product	Netbotz
Number of rack unit	1U
Provided Equipment	Cable ties Documentation CD Installation guide Temperature/Humidity Sensor

Physical

Height	1.7 in (4.3 cm)
Width	13.3 in (33.7 cm)
Depth	1.7 in (4.3 cm)
Net Weight	1.34 lb(US) (0.61 kg)
Mounting Location	Front
Mounting preference	No preference
Mounting Mode	Rack-mounted

Conformance

Standards	FCC Part 15 class A ICES-003
Product Certifications	AS/NZS 3548 (C-Tick) Class A CE GOST NOM VCCI Class A

Environmental

Ambient Air Temperature for Operation	32...113 °F (0...45 °C)
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...149 °F (-15...65 °C)
Storage altitude	0...50000 ft (0...15240 m)

Ordering and shipping details

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

GTIN	731304757009
------	--------------

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.5 in (6.4 cm)
Package 1 Width	18.0 in (45.7 cm)
Package 1 Length	8.7 in (22.2 cm)
Package weight(Lbs)	4.004 lb(US) (1.816 kg)

Compliance

Compliance	TAA Compliant
------------	---------------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	246 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	19 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.3 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.3 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	224 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	3 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	49
Circularity Profile	End of Life Information
Removable battery	No
Take-back	Nej

Image of product / Alternate images

Alternative



