

# Product data sheet

Specifications



## APC NetShelter SX Advanced Rack, High Strength, 48U, 2258H x 750W x 1470D mm, with Shock Package, Black [TAA]

AR9657SPB2

### Overview

Lead time Usually in Stock

### Main

Product or Component Type	Rack enclosure
Number of rack unit	48U
Provided equipment	Baying hardware Key(s) Leveling feet Mounting Hardware Pre-installed casters Side Panels

### Physical

Height	88.8 in (2256 mm)
Width	29.5 in (750 mm)
Depth	57.9 in (1470 mm)
Net Weight	637.1 lb(US) (289 kg)
Color	Black
Mounting preference	No preference
Mounting Mode	Not rack-mountable
Maximum Mounting Depth	52.0 in (1320.8 mm)
Minimum Mounting Depth	11.5 in (292 mm)
Rack Width	19"
Marking	12 gauge EIA mounting rail 16 gauge front door 16 gauge post 18 gauge rear door 18 gauge roof 18 gauge side panels
Permanent permissible load	4250 lb(US) (1927.8 kg) static 3500 lb(US) (1587.6 kg) dynamic

### Conformance

Standards	EIA-310E UL 2416
-----------	---------------------

### Ordering and shipping details

GTIN 731304762591

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Packing Units

---

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	98.1 in (249.2 cm)
Package 1 Width	43.5 in (110.5 cm)
Package 1 Length	64.4 in (163.5 cm)
Package weight(Lbs)	815.7 lb(US) (370 kg)

---

## Compliance

---

Compliance	TAA Compliant BAA Compliant via COTS
------------	---

---



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	2 999 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	1 976 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	110 kg CO2 eq.
Carbon footprint of the installation phase [A5]	43 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	887 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	31346aed-552c-4a16-81d9-e683a383b6da
EU RoHS Directive	<a href="#">Compliant</a>
REACH Regulation	<a href="#">Free of Substances of Very High Concern above the threshold</a>

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	97
Circularity Profile	No need of specific recycling operations
Removable battery	No
Take-back	Nej
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

---

