

# Product data sheet

Specifications



## APC NetShelter SX, Server Rack Enclosure, 45U, White, 2124H x 600W x 1070D mm [TAA]

AR3105W

⚠ Discontinued on: Oct 31, 2025

⚠ To be end-of-service on: Sep 1, 2026

⚠ To be discontinued

## Overview

Lead time Usually in Stock

## Main

Product or Component Type	Rack enclosure
Number of rack unit	45U
Provided equipment	Baying hardware Key(s) Keyed-alike doors and side panels Leveling feet Mounting Hardware Pre-installed casters Side Panels User Manual

## Physical

Height	83.6 in (2124 mm)
Width	23.6 in (600 mm)
Depth	42.1 in (1070 mm)
Net Weight	302.03 lb(US) (137 kg)
Color	White
Mounting preference	No preference
Mounting Mode	Not rack-mountable
Maximum Mounting Depth	36.02 in (914.9 mm)
Minimum Mounting Depth	7.5 in (191 mm)
Rack Width	19"
Marking	14 gauge EIA mounting rail 16 gauge front door 16 gauge post 18 gauge rear door 18 gauge roof 18 gauge side panels
Permanent permissible load	2250 lb(US) (1020.6 kg) dynamic 3750 lb(US) (1701.0 kg) static

## Conformance

Standards	UL 2416 UL 60950-1 EIA-310E
-----------	-----------------------------------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Ordering and shipping details

---

GTIN 731304322450

## Packing Units

---

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	88.2 in (224 cm)
Package 1 Width	48.03 in (122 cm)
Package 1 Length	29.4 in (74.6 cm)
Package weight(Lbs)	338.9 lb(US) (153.7 kg)

## Compliance

---

Compliance TAA Compliant  
BAA Compliant via COTS

## Contractual warranty

---

Warranty (in months) 60



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	539 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	515 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	13 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	11 kg CO2 eq.

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	<a href="#">Compliant</a>
REACH Regulation	<a href="#">Free of Substances of Very High Concern above the threshold</a>

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	95
Take-back	Nej
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

---





