

5 Port Unmanaged Industrial Ethernet Switch

IES5102



*actual product may vary from photos

DE: Bedienungsanleitung - de.startech.com

FR: Guide de l'utilisateur - fr.startech.com

ES: Guía del usuario - es.startech.com

IT: Guida per l'uso - it.startech.com

NL: Gebruiksaanwijzing - nl.startech.com

PT: Guia do usuário - pt.startech.com

For the most up-to-date information, please visit: www.startech.com

FCC Compliance Statement

This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Changes or modifications not expressly approved by StarTech.com could void the user's authority to operate the equipment.

Industry Canada Statement

This Class A digital apparatus complies with Canadian ICES-003.

Cet appareil numérique de la classe [A] est conforme à la norme NMB-003 du Canada.

CAN ICES-3 (A)/NMB-3(A)

Use of Trademarks, Registered Trademarks, and other Protected Names and Symbols

This manual may make reference to trademarks, registered trademarks, and other protected names and/or symbols of third-party companies not related in any way to StarTech.com. Where they occur these references are for illustrative purposes only and do not represent an endorsement of a product or service by StarTech.com, or an endorsement of the product(s) to which this manual applies by the third-party company in question. Regardless of any direct acknowledgement elsewhere in the body of this document, StarTech.com hereby acknowledges that all trademarks, registered trademarks, service marks, and other protected names and/or symbols contained in this manual and related documents are the property of their respective holders.

Table of Contents

Introduction	1
Packaging Contents	1
System Requirements.....	1
Product Diagram	2
Front View	2
LED Indicators.....	2
Rear & Side View	2
Installation	3
DIN Rail Mounting.....	3
Connecting to Power	3
Network Connection.....	4
Specifications	5
Technical Support	7
Warranty Information	7

Introduction

Packaging Contents


- 1x 5 Port Ethernet Switch (w/ Attached DIN Rail Bracket)
- 1x Terminal Block
- 1x Instruction Manual CD

System Requirements

- 2 or 3-wire 12~48V DC power source
- 10/100Mbps compatible Ethernet network
- RJ45 terminated Ethernet cabling (Cat 5 or better recommended)

Product Diagram

Front View




LED Indicators

The IES5102 has LED indicators for each of the RJ45 ports on the switch to show the status of each connection

LED	State	Indication
LINK/ACT (Green)	Steady	Valid network connection established (Link)
	Flashing	Transmitting or receiving data (Activity)
100 (Amber)	Steady	Port is transferring at 100Mbps
	Off	Port is transferring at 10Mbps or is not transferring


Rear & Side View



Installation

DIN Rail Mounting

1. Hook the top, fixed DIN rail bracket on the rear of the Ethernet Switch to the top edge of the DIN rail.
2. Push the lower portion of the Ethernet Switch back against the DIN rail, which will cause the bottom, spring-loaded DIN clip to snap in place.
3. To remove the Ethernet Switch from the DIN rail, pull the small tab on the bottom of the spring-loaded clip to release it.



Connecting to Power

1. If already inserted into the Ethernet Switch, gently, yet firmly pull the terminal block connector housing from the Ethernet Switch.
2. Using a small flat head screw driver, loosen the screws for the terminal block connectors.
3. Connect the power and ground wires from your DC power source to the proper terminal block connectors and fasten the screws. The terminals are marked on the Ethernet Switch housing.



4. Reinsert the terminal block housing into the Ethernet Switch.

Network Connection

1. Ensure that both the IES5102 and any devices that are to be connected to it are powered off.
2. Prepare the necessary cabling for each device that is to be attached to the IES5102. Use the following chart as reference for cabling types:

Speed	Connector	Port Speed (Half/ Full Duplex)	Cable Type	Max. Distance
10Base-T	RJ45	10/20 Mbps	2-pair UTP/STP Cat 5 or better	100 m
100Base-TX	RJ45	100/200 Mbps	2-pair UTP/STP Cat. 5	100 m

3. Connect your uplink (connection to an upstream network switch) to the Uplink Port, followed by connecting your network devices to the remaining RJ45 ports using RJ45 terminated Ethernet cabling (Cat 5 or better recommended).
4. Check to ensure that both devices are transmitting and receiving data by checking their LED displays.

Specifications

Ports	5
Industry Standards	IEEE 802.3 (10BASE-T), IEEE 802.3u (100BASE-TX), IEEE 802.3az (Energy Efficient Ethernet)
External Ports	5 - RJ-45 Female 1 - Terminal Block (3 Wire)
Maximum Data Transfer Rate	200 Mbps (Full-Duplex), 100 Mbps (Half-Duplex)
Maximum Cable Length	328 ft [100 m]
Flow Control	IEEE 802.3x Full-Duplex
Compatible Networks	10/100 Mbps
Auto MDIX	Yes
Full Duplex Support	Yes
Switching Architecture	Store-and-Forward Auto-Negotiation
MTBF	1,179,133 Hours
Supported Protocols	IEEE 802.1P Quality of Service (QoS)
OS Compatibility	OS Independent; No additional drivers or software required
Color	Black
Enclosure Type	Plastic
Product Dimensions (LxWxH)	70mm x 26mm x 110mm
Product Weight	7.1 oz [200 g]
LED Indicators	1 - Power 5 - Link/Activity 5 - Activity (100 Mbps)
Power Source	Terminal Block

Input Voltage	12 ~ 48 DC
Input Current	0.05 A ~ 0.2 A
Power Consumption	2.12W Max
Operating Temperature	-10°C to 60°C (14°F to 140°F)
Storage Temperature	-25°C to 85°C (-13°F to 185°F)
Humidity	5~95% RH (Non-Condensing)

Technical Support

StarTech.com's lifetime technical support is an integral part of our commitment to provide industry-leading solutions. If you ever need help with your product, visit www.startech.com/support and access our comprehensive selection of online tools, documentation, and downloads.

For the latest drivers/software, please visit www.startech.com/downloads

Warranty Information

This product is backed by a two year warranty.

In addition, StarTech.com warrants its products against defects in materials and workmanship for the periods noted, following the initial date of purchase. During this period, the products may be returned for repair, or replacement with equivalent products at our discretion. The warranty covers parts and labor costs only. StarTech.com does not warrant its products from defects or damages arising from misuse, abuse, alteration, or normal wear and tear.

Limitation of Liability

In no event shall the liability of StarTech.com Ltd. and StarTech.com USA LLP (or their officers, directors, employees or agents) for any damages (whether direct or indirect, special, punitive, incidental, consequential, or otherwise), loss of profits, loss of business, or any pecuniary loss, arising out of or related to the use of the product exceed the actual price paid for the product. Some states do not allow the exclusion or limitation of incidental or consequential damages. If such laws apply, the limitations or exclusions contained in this statement may not apply to you.

Hard-to-find made easy. At StarTech.com, that isn't a slogan. It's a promise.

StarTech.com is your one-stop source for every connectivity part you need. From the latest technology to legacy products — and all the parts that bridge the old and new — we can help you find the parts that connect your solutions.

We make it easy to locate the parts, and we quickly deliver them wherever they need to go. Just talk to one of our tech advisors or visit our website. You'll be connected to the products you need in no time.

Visit www.startech.com for complete information on all StarTech.com products and to access exclusive resources and time-saving tools.

StarTech.com is an ISO 9001 Registered manufacturer of connectivity and technology parts. StarTech.com was founded in 1985 and has operations in the United States, Canada, the United Kingdom and Taiwan servicing a worldwide market.