

1. Identification

Product identifier Dymon® Do-It ALL

Other means of identification
Part Number 08020

Recommended use Surface Disinfectant

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information
Manufacturer
Company name ITW Pro Brands
Address 805 E. Old 56 Highway
 Olathe, KS 66061
Country (U.S.A.)
 Tel: +1 800-443-9536
In Case of Emergency 1-800-535-5053 (Infotrac)

2. Hazard(s) identification

Physical hazards	Gases under pressure	Liquefied gas
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Sensitization, skin	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements



Signal word Warning

Hazard statement Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

Precautionary statement

Prevention	Avoid breathing gas. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear eye protection/face protection. Wear protective gloves.
Response	If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
Storage	Protect from sunlight. Store in a well-ventilated place.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Diethylene Glycol Monobutyl Ether		112-34-5	1 - 10
Petroleum Gases, Liquefied, Sweetened		68476-86-8	1 - 10

Chemical name	Common name and synonyms	CAS number	%
Isopropanol		67-63-0	1 - 5
Potassium Hydroxide		1310-58-3	1 - 5
Versene		60-00-4	1 - 5
Alcohols, C9-11, Ethoxylated		68439-46-3	0.1 - 1
Alkyl Dimethyl Benzyl Ammonium Chloride (C12-18)		68391-01-5	0.1 - 1
Ammonium Hydroxide		1336-21-6	0.1 - 1
d-limonene		5989-27-5	0.1 - 1
Sodium Nitrate		7632-00-0	0.1 - 1

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Not likely, due to the form of the product. Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. ALWAYS stay away from tanks engulfed in flame. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Cool containers exposed to flames with water until well after the fire is out.
General fire hazards	Contents under pressure. Pressurized container may explode when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	--

Methods and materials for containment and cleaning up

Isolate area until gas has dispersed.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Avoid discharge into drains, water courses or onto the ground.

Environmental precautions**7. Handling and storage****Precautions for safe handling**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Isopropanol (CAS 67-63-0)	PEL	980 mg/m3 400 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
DIETHYLENE GLYCOL MONOBUTYL ETHER (CAS 112-34-5)	TWA	10 ppm	Inhalable fraction and vapor.
Isopropanol (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	
Potassium hydroxide (CAS 1310-58-3)	Ceiling	2 mg/m3	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	1225 mg/m3 500 ppm
	TWA	980 mg/m3 400 ppm
Potassium hydroxide (CAS 1310-58-3)	Ceiling	2 mg/m3

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Isopropanol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Gas.

Form Liquefied gas.

Color Colorless.

Odor Citrus and Ammonia.

Odor threshold Not available.

pH 12.2

Melting point/freezing point Not available.

Initial boiling point and boiling range Not available.

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available.

Flammability limit - upper (%) Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Complete.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Density 8.34 lbs/gal

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Specific gravity 1
VOC 7.90 % per US State and Federal Consumer Product Regulations

10. Stability and reactivity

Reactivity Reacts violently with strong acids. This product may react with oxidizing agents.
Chemical stability Material is stable under normal conditions.
Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.
Conditions to avoid Heat. Contact with incompatible materials. Do not mix with other chemicals.
Incompatible materials Acids. Oxidizing agents.
Hazardous decomposition products Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.
Skin contact Causes skin irritation. May cause an allergic skin reaction.
Eye contact Causes serious eye irritation.
Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components	Species	Test Results
Alcohols, C9-11, Ethoxylated (CAS 68439-46-3)		
Acute		
Dermal		
LD50	Rabbit	2000 mg/kg, 24 Hours
Ammonium Hydroxide (CAS 1336-21-6)		
Acute		
Oral		
LD50	Rat	350 mg/kg
Diethylene Glycol Monobutyl Ether (CAS 112-34-5)		
Acute		
Dermal		
LD50	Rabbit	2700 mg/kg
Oral		
LD50	Rat	3300 mg/kg
d-limonene (CAS 5989-27-5)		
Acute		
Oral		
LD50	Rat	> 2000 mg/kg
Isopropanol (CAS 67-63-0)		
Acute		
Oral		
LD50	Rat	4.7 g/kg
Potassium Hydroxide (CAS 1310-58-3)		
Acute		
Oral		
LD50	Rat	270 mg/kg

Components	Species	Test Results
Sodium Nitrate (CAS 7632-00-0)		
Acute		
Inhalation		
LC50	Rat	5.5 mg/l, 4 Hours
Versene (CAS 60-00-4)		
Acute		
Oral		
LD50	Rat	> 2000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	May cause an allergic skin reaction.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
ACGIH Carcinogens		
Isopropanol (CAS 67-63-0)	A4 Not classifiable as a human carcinogen.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
d-limonene (CAS 5989-27-5)	3 Not classifiable as to carcinogenicity to humans.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)		
	Not listed.	
US. National Toxicology Program (NTP) Report on Carcinogens		
	Not listed.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not likely, due to the form of the product.	
Chronic effects	Prolonged inhalation may be harmful.	

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
Alcohols, C9-11, Ethoxylated (CAS 68439-46-3)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 2.9 - 8.5 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) 6 - 12 mg/l, 96 hours
Ammonium Hydroxide (CAS 1336-21-6)		
Aquatic		
Fish	LC50	Western mosquitofish (Gambusia affinis) 15 mg/l, 96 hours
Diethylene Glycol Monobutyl Ether (CAS 112-34-5)		
Aquatic		
Fish	LC50	Bluegill (Lepomis macrochirus) 1300 mg/l, 96 hours
d-limonene (CAS 5989-27-5)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia pulex) 69.6 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) 0.619 - 0.796 mg/l, 96 hours

Components	Species	Test Results
Isopropanol (CAS 67-63-0)		
Aquatic		
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>) > 1400 mg/l, 96 hours
Potassium Hydroxide (CAS 1310-58-3)		
Aquatic		
Fish	LC50	Western mosquitofish (<i>Gambusia affinis</i>) 80 mg/l, 96 hours
Sodium Nitrate (CAS 7632-00-0)		
Aquatic		
Crustacea	EC50	Greasyback shrimp (<i>Metapenaeus ensis</i>) 16.14 - 26.61 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (<i>Oncorhynchus mykiss</i>) 0.15 - 0.25 mg/l, 96 hours
Versene (CAS 60-00-4)		
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>) 113 mg/l, 48 hours
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>) 34 - 62 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Diethylene Glycol Monobutyl Ether	0.56
d-limonene	4.232
Isopropanol	0.05

Mobility in soil Not established.

Other adverse effects None known.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

D002: Waste Corrosive material [pH <=2 or =>12.5, or corrosive to steel]
D003: Waste Reactive material

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, non-flammable, (each not exceeding 1 L capacity)
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Label(s)	2.2
Packing group	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

IATA

UN number	UN1950
------------------	--------

UN proper shipping name	Aerosols, non-flammable
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Packing group	Not available.
Environmental hazards	No.
ERG Code	2L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

UN number	UN1950
UN proper shipping name	Aerosols, non-flammable
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Packing group	Not available.
Environmental hazards	
Marine pollutant	No.
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

DOT



IATA; IMDG



General information

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Sodium Nitrate (CAS 7632-00-0)

0.1 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

Ammonium Hydroxide (CAS 1336-21-6)

Listed.

Potassium Hydroxide (CAS 1310-58-3)

Listed.

Sodium Nitrate (CAS 7632-00-0)

Listed.

Versene (CAS 60-00-4)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**SARA 302 Extremely hazardous substance**

Not listed.

SARA 311/312 Hazardous chemical

Yes

Classified hazard categoriesGas under pressure
Skin corrosion or irritation
Serious eye damage or eye irritation
Respiratory or skin sensitization**SARA 313 (TRI reporting)**

Not regulated.

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Isopropanol (CAS 67-63-0)

Low priority

US state regulations**US. New Jersey Worker and Community Right-to-Know Act**

Ammonium Hydroxide (CAS 1336-21-6)

Isopropanol (CAS 67-63-0)

Potassium Hydroxide (CAS 1310-58-3)

Sodium Nitrate (CAS 7632-00-0)

Versene (CAS 60-00-4)

California Proposition 65California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

Isopropanol (CAS 67-63-0)

Petroleum Gases, Liquefied, Sweetened (CAS 68476-86-8)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 06-18-2019

Version # 01

Disclaimer ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.