

Safety Data Sheet

According to OSHA 29 CFR 1910.1200 HCS & Canada WHMIS

Revision Date : 02.10.2013

SECTION 1: Identification

1.1. Product identifier

Product Name : Xstamper Refill Ink Color : (Black)
 CS-10N, CS-20N, CS-60N
 Xstamper Products
 Dyestuff type Xstamper Color : (Black)
 CX-AN, CX-BN, CX-GN, CX-FN, CA-2N, CA-3N, etc.



1.2. Recommended use of the chemical and restrictions on use

Recommended use : Stamp ink

1.3. Details of the supplier of the safety data sheet

Supplier	Company Name	: Shachihata Inc.
	Address	: 1661 W 240th Street Harbor City CA 90710
	Telephone	: 310-530-4445
	Fax	: 310-530-2892
	Contact (e-mail)	: customerservice@xstamper.com
Manufacturer	Company Name	: Shachihata Inc.
	Address	: 4-69, Amazuka-cho, Nishi-ku, Nagoya City, 451-0021, Japan
	Telephone	: +81-52-521-3600
	Fax	: +81-52-521-3899
	Contact (e-mail)	: chem-analysis@ngy.shachihata.co.jp



1.4. Emergency telephone number

Telephone : 800-541-9719 ext. 6466

SECTION 2: Hazard(s) identification

United States (US) : According to OSHA 29 CFR 1910.1200 HCS 2012

2.1.1 Classification of the substance or mixture

Flammable liquids, Category 3	H226	: Flammable liquid and vapour
Serious eye damage /eye irritation, Category 2B	H320	: Causes eye irritation

2.1.2 Label elements

Hazard pictograms :



Signal word	: Warning	
Hazard statement	: Flammable liquid and vapour	(H226)
	: Causes eye irritation	(H320)

Precautionary statement

【Prevention】

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.	(P210)
Take precautionary measures against static discharge.	(P243)
Wear protective gloves/protective clothing/eye protection/face protection.	(P280)
Wash hands thoroughly after handling.	(P264)

【Response】

In case of fire : Use dry chemical powder, form or carbon dioxide for extinction.	(P370+P378)
IF INHALED : Remove victim to fresh air and keep at rest in a position comfortable for breathing.	(P304+P340)
IF IN EYES : Rinse cautiously with water for several minutes.	(P305+P351+P338)
Remove contact lenses, if present and easy to do. Continue rinsing.	
If eye irritation persists : Get medical advice/attention.	(P337+P313)

IF SWALLOWED : Get medical advice/attention if you feel unwell. Rinse mouth.

(P301+P314+P330)

【Storage】

Store in a well-ventilated place. Keep container tightly closed.

(P403+P233)

【Disposal】

Dispose of contents/container to waste in accordance with
local/regional/ national/international regulation (to be specified).

(P501)

2.1.3 Other hazards

Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard),
this product is considered hazardous.

Canada : According to WHMIS

2.2.1 Classification of the substance or mixture

Class B2 : Flammable Liquids

Class D2B : Eye irritation


2.2.2 Label elements




2.2.3 Other hazards

In Canada, the product mentioned above is considered hazardous
under the Workplace Hazardous Materials Information System (WHMIS)

2.3 Other information



HMIS



SECTION 3: Composition/information on ingredients

Substance/Mixture : Mixture
Ingredients :

Chemical Name / Generic name	Composition weight %	CAS Registry No.	Classification (OSHA HCS 2012)	
			Hazard Class	Hazard statement
Ethanol	1 ~ 10	64-17-5	Flam.Liq. 2	H225
Derivative of vegetable oil	40 ~ 50	Confidential	none	none
1,2-Propylene glycol	5 ~ 15	57-55-6	none	none
2-(2-butoxyethoxy)ethanol	5 ~ 15	112-34-5	Eye Irrit.2A	H319
Vegetable oil	5 ~ 15	Confidential	none	none
Synthetic resin	5 ~ 15	Confidential	none	none
Dyestuff	5 ~ 15	Confidential	none	none
total	100			

SECTION 4: First-aid measures

4.1. Description of first aid measures

IF INHALED : Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Consult a doctor if symptoms persist.

IF ON SKIN : Remove/Take off immediately all contaminated clothing. Wash with soap and water.
If skin irritation/rash occurs or feel unwell, consult a doctor for medical advice.

IF IN EYES : Rinse cautiously with water for several minutes. Remove contact lenses, if present and
easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

IF SWALLOWED : After rinse mouth immediately, give about 250 ml of water or milk and thin in the stomach,
and do not vomit forcibly. Moreover, do not give anything from the mouth to the patient
when not conscious. Receive the doctor's treatment (stomach pump) promptly.

Note to Physicians :

All treatments should be based on observed signs and symptoms of distress in the patient.

Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry chemical powder, foam or carbon dioxide

Unsuitable extinguishing media : Water jet

5.2. Special hazards arising from the substance or mixture

For initial stage extinction, carbon dioxide or dry chemical powder.

When a fire extends, fire is extinguished by a large amount of water spray.

Do not discharge extinguishing waters into the aquatic environment.

5.3. Advice for firefighters

In the extinction work, an appropriate protective equipment (gloves, glasses, and mask) has to be worn.

Because during a fire, hazardous gases may be generated, fire-fighters have to wear self-contained breathing apparatus and other protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe area. Shut off all sources of ignition.

No Flares, smoking or flame in area. Put on protective equipment. Ensure adequate ventilation.

6.2. Environmental precautions

Do not throw the leakage thing directly into environment

6.3. Methods and material for containment and cleaning up

In case of a small spill, absorb with dry sand, soil, sawdust, cloth, etc., then place in a chemical waste containers.

In case of large spills, dike and prevent overflow, cover spills with foam, then place in a chemical container using non-sparking tools.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling : Use with adequate ventilation.

Avoid contact with skin, eyes and clothing.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage : Keep containers tightly closed and store in a cool and dry place.
areas and containers

Keep away from heat and flame, ignition source and sunlight.

Keep out of the reach of children.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ACGIH (2013)

Ethanol	STEL	1000ppm
---------	------	---------

2-(2-butoxyethoxy)ethanol	TWA	10ppm
---------------------------	-----	-------

OSHA PEL

Ethanol	TWA	1000ppm
---------	-----	---------

Canada Ontario Provincial

Ethanol	STEL	1000ppm
---------	------	---------

1,2-Propylene glycol	TWA	50ppm
----------------------	-----	-------

Canada Quebec Provincial

Ethanol	TWA	1000ppm
---------	-----	---------

8.2. Exposure controls

Personal protective equipment

Respiratory Protection : Use with local exhaust ventilation, when in long use.

Avoid breathing vapours. Wear mask to prevent organic gas, if necessary.

Hand Protection : Avoid contact with hands. Wear safety gloves, if necessary.

Eye Protection : Avoid contact with eyes. Wear safety glasses, if necessary.

Skin Protection : Avoid skin contact. Wear personal protection apron, boots, if necessary.

Environmental exposure controls

General advice : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : black liquid
Odor : none
pH : Not applicable
Boiling point : No data available
Flash point : 104 °F (40 °C) (closed cup)
Relative Density (at 77 °F, 25 °C) : 1.0 (g/cm³)
Solubility in Water : Insoluble

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.3. Chemical stability

The product is stable.

10.4. Conditions to Avoid

High temperature, Direct sunlight, Fire

10.5. Incompatible Materials

No data available

10.6. Hazardous decomposition products

CO, CO₂

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : LD/LC50 values that are relevant for classification
[Ethanol]
Oral-rat LD50 7,060mg/kg
Inhalation-rat LC50 20,000ppm/10h
[2-(2-butoxyethoxy)ethanol]
Oral-rat LD50 5,660mg/kg
Dermal-rabbit LD50 2,700mg/kg

Serious eye damage /eye irritation : Category 2B Causes eye irritation

Carcinogenicity : This product does not contain any component that is considered a human carcinogen by IARC, ACGIH, OSHA or NTP.

SECTION 12: Ecological information

12.1. Ecotoxicity : No data available
12.2. Persistence and degradability : No data available
12.3. Bioaccumulative potential : No data available
12.4. Mobility in soil : No data available
12.5. Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal must be made according to official regulations.
Comply with all Federal, State, and Local regulations regarding disposal.
Do not allow product to reach ground, any water course or sewage system.

SECTION 14: Transport information

14.1. UN number	DOT, TDG, IMO / IMDG, IATA / ICAO	: UN1210
14.2. UN proper shipping name	DOT, TDG, IMO / IMDG, IATA / ICAO	: PRINTING INK,flammable
14.3. Transport hazard class(es)	DOT, TDG, IMO / IMDG, IATA / ICAO	:
	- Class	3 (Flammable liquids.)
	- Label	3
14.4. Packing group	DOT, TDG, IMO / IMDG, IATA / ICAO	: III
14.5. Environmental hazards	Marine pollutant	: No
14.6. Special precautions for user	EMS Number	: F-E,S-D
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code		: Not applicable.

**SECTION 15: Regulatory information**

< USA Information >

OSHA STATUS	: This product is hazardous under 29 CFR 1910.1200.
TSCA inventory	: All components of this product are listed in the TSCA Inventory.
TSCA Hazard Communication Program (40 CFR Part 721) (SNUR)	: not Listed
EPCRA Section 302 Extremely Hazardous Substances (EHS)	: not Listed
EPCRA Section 313 Toxic Chemicals	: not Listed
CERCLA Hazardous Substances	: not Listed
CAA Section 112(r) List of Substances for Accidental Release Prevention	: not Listed
California Proposition 65	: not Listed

< Canada Information >

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

Canada inventory : All components of this product are listed in the DSL/NDL Inventory.

WHMIS Ingredient Disclosure List (SOR/88-64) : Ethanol , 1,2-Propylene glycol ,
(WHMIS : Canadian Workplace Hazardous Material Information System) 2-(2-butoxyethoxy)ethanol

SECTION 16: Other information, including date of preparation or last revision

Last Revision Date :
Preparation Date : 02.10.2013



EU RoHS Directive(2002/95/EC) and ELV Directive(2000/53/EC)
This product does not contain lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB) or polybrominated diphenylethers (PBDE).

This data sheet may not be enough when evaluating danger or hazard. The above information, which is created from currently available documents, information and data, may be revised when new findings are announced. This document has been written on the assumption that when dealing with a large amount of ink on the business case and emergency. When handling as a normal product, please refer to the notes that are described in the produce or packaging. The information contained herein is not intended to provide any kind of warranty other than information; there is no guarantee for the accuracy of the content.