

1. IDENTIFICATION OF THE SUBSTANCE PREPARATION AND COMPANY UNDERTAKING

1.1 PRODUCT IDENTIFIER

Product name: Xerox Phaser 4600/4620 High Yield Toner Cartridge

Part number: ELI76235

1.2 IDENTIFIED USES AND USES ADVISED AGAINST

For use in: This mixture is a toner used in copiers/printers.

1.3 **SUPPLIER DETAILS**

Supplier: SP Richards Co.

6300 Highlands Parkway Smyrna, GA 30082 United States

Phone number: 815-431-8100

Fax: 815-461-8583

Contact Hours: 08:00AM-5:00PM CST

1.4 **EMERGENCY TELEPHONE NUMBERS**

Supplier: 815-431-8100

2. HAZARDS IDENTIFICATION

2.1 INFORMATION and CLASSIFICATION

Overview: The product is classified and labeled according to the Globally Harmonized System (GHS). Skin

corrosion/irritation (Category 2). Serious eye damage/eye irritation (Category 1). Specific target organ toxicity - single exposure (Category 3). Specific target organ toxicity - repeated exposure (Category 2).

The hazards not mentioned are not applicable or no data available.

2.2 **LABEL ELEMENTS**

Applicable Pictograms:

NO PICTOGRAM

Danger Indications: Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. May cause damage

to organs through prolonged or repeated exposure.

Risk Phrases: N/A Safety Phrases: N/A

2.3 OTHER HAZARDS

PBT or vPvB: N/A

Product: Xerox Phaser 4600/4620 High Revision date: 02/26/2018 Page: 1/9

^{*} This document provides safety-related information about toner contained in print cartridge for use in laser printer



3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients	CAS number	Weight %	OSHA PEL	ACGIH TLV	Other
Resin (polystyrene- acrylate)		58			
Magnetic powder (triiron tetraoxide)	1317-61-9	37			EC NUMBER: 215-277-5
Poly propylene wax					
Salicylic acid E8I	69-72-7				EC NUMBER: 200-712-3
Silicon dioxide	7631-86-9				EC NUMBER: 231-545-4
Cerium oxide	1306-38-3				EC NUMBER: 215-150-4

The Full Text for all R-Phrases are Displayed in Section 16

COMPOSITION COMMENTS

The Data Shown is in accordance with the latest Directives.

This section provides composition information for the toner powder contained in specially designed container inside of the print cartridge.

4. FIRST-AID MEASURES

4.1 FIRST AID MEASURES

Skin contact:

4.1.1 FIRST AID INSTRUCTIONS BY RELEVANT ROUTES OF EXPOSURE

Inhalation: If inhaled, remove to fresh air. If necessary, get medical attention.

Eye contact: In case of contact with eyes, flush with copious amounts of water for at least 15 minutes. Assure

adequate flushing by separating the eyelids with fingers. If irritation persists, call a physician. In case of contact, immediately wash skin with soap and copious amounts of water. If irritation

persists, call a physician.

Ingestion: If swallowed, immediately wash out mouth with water provided person is conscious. Call a

physician.

4.1.2 ADDITIONAL FIRST AID INFORMATION

Additional first aid information: N/A Immediate Medical Attention Required: N/A

4.2 **SYMPTOMS AND EFFECTS**

Acute Symptoms from Exposure: N/A
Delayed Symptoms from Exposure: N/A

4.3 IMMEDIATE SPECIAL TREATMENT OR EQUIPMENT REQUIRED

N/A

Product: Xerox Phaser 4600/4620 High Revision date: 02/26/2018 Page: 2/9



5. FIRE-FIGHTING MEASURES

5.1 EXTINGUISHING MEDIA

Recommended Extinguishing Media: Water spray, Dry chemical, Carbon dioxide or appropriate foam.

Extinguishing Media Not to be Used: N/A

5.2 **SPECIAL HAZARD**

Unusual Fire/Explosion Hazards: N/A Extinguishing Media Not to be Used: N/A

5.3 ADVICE FOR FIRE FIGHTERS

Avoid inhalation of smoke. Wear protective cloting an wear self-contained breathing apparatus

6. ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

6.1.1 PRECAUTIONS FOR NON-EMERGENCY PERSONNEL

Exercise appropriate precautions to minimize direct contact with skin or eyes and prevent inhalation of dust.

6.1.2 ADDITIONAL FIRST AID INFORMATION

N/A

6.1.3 PERSONAL PROTECTION

Wear personal protective equipment as described in Section 8.

6.2 **ENVIRONMENTAL PRECAUTIONS**

Regulatory Information: Keep product out of sewers and watercourses.

6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANUP

Spill or Leak Cleanup Procedures: Sweep up with spade and transfer to a dry, clean, lidded container for disposal. Avoid raising

dust. Ventilate area and wash spill site after material pickup is complete.

Product: Xerox Phaser 4600/4620 High Revision date: 02/26/2018 Page: 3/9



7. HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Recommendations for Handling: No special precautions when used as intended. Keep containers closed, avoid creating dust.

Keep away from ignition sources.

Advice on General Hygiene: Never eat, drink or smoke in work areas. Practice good personal hygiene after using this

material, especially before eating, drinking, smoking, using the restroom, or applying

cosmetics.

7.2 **CONDITIONS FOR SAFE STORAGE**

Avoid high temperatures, >100°F/32°C

7.3 **SPECIFIC END USES**

Printing devices

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 **CONTROL PARAMETERS**

The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release in order to maintain airborne concentrations of the product below OSHA PELs (See Section 3).

Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

8.2 **EXPOSURE CONTROLS**

Respiratory protection:

IMPROPER USE OF RESPIRATORS IS DANGEROUS. Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134 and 1910.137) and, if necessary, wear a NIOSH approved respirator. Select respirator based on its suitability to provide adequate worker protection for given work conditions, levels of airborne contamination, and sufficient levels of oxygen.

Eye/Face Protection:

Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Hand/Skin Protection:

For emergency or non-routine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. WARNING! Air purifying respirators do not protect worker in oxygen deficient atmospheres.

Additional Protection:

N/A

Protective Clothing and Equipment:

Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear splashproof chemical goggles and face shield when working with liquid, unless full face piece respiratory protection is worn.

Safety Stations:

Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Contaminated Equipment:

Separate contaminated work clothes from street clothes. Launder before reuse. Remove material from your shoes and clean personal protective equipment. Never take home contaminated clothing.

Comments:

Never eat, drink or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the restroom, or applying cosmetics.

Product: Xerox Phaser 4600/4620 High Revision date: 02/26/2018 Page: 4/9



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 **DETAIL INFORMATION**

Physical state: APPEARANCE: Black powder

Color: Black

Odor: Weak odor

Odor threshold: N/A

Boiling point: N/A

Melting point: >350°C

Flash point: N/A

Explosion limits: N/A

Relative density: N/A

Auto-ignition temperature: N/A

9.2 OTHER INFORMATION

pH Value: 9.4 (25°C, 50.Og/L). Solubility: Slightly soluble in water

10. CHEMICAL STABILITY AND REACTIVITY

10.1 Reactivity:

Reactivity Hazards: None

Data on Mixture Substances: None

10.2 **Chemical Stability:** The product is stable. Under normal conditions of storage and use, hazardous

polymerisation will not occur.

10.3 **Hazardous Polymerization:** Stable under conditions of normal use.

10.4 **Conditions to Avoid:** Keep away from heat, flame, sparks and other ignition sources.

10.5 **Incompatible Materials:** Strong oxidising materials

10.6 Hazardous Decomposition: Will not occur.

Product: Xerox Phaser 4600/4620 High Yield Toner Cartridge Revision date: 02/26/2018 Page: 5/9



11. INFORMATION ON TOXICOLOGICAL EFFECT

Mixtures: N/A

Salicylic acid: Oral: LD50 rat 891mg/kg. Inhalation: LC50 rat >900mg/m3/1H. Dermal: LD50 rabbit **Acute Toxicity:**

>IOOOOmg/kg. Cerium oxide: Oral rat LD50: >5000mg/kg.

Skin Corrosion/Irritation: Causes skin irritation.

Serious Eye Damage: Causes serious eye damage.

Inhalation: N/A Sensitization: N/A **Mutagenicity:** N/A Carcinogenicity: N/A Reproductive Toxicity: N/A

May cause respiratory irritation. STOT - Single Exposure:

STOT - Multiple Exposure: May cause damage to organs through prolonged or repeated exposure.

Ingestion:

Hazard Class Information: N/A **Mixture on Market Data:** N/A Symptoms: N/A Delayed/Immediate Effects: N/A Test Data on Mixture: N/A Not Meeting Classification: N/A Routes of Exposure: N/A

Interactive Effects: N/A **Absence of Specific Data:** N/A Mixture vs Substance Data: N/A

12. ECOLOGICAL INFORMATION

Salicylic acid: Toxicity to fish LC50 - Leuciscus idus (Golden orfe) - 90 mg/1. Toxicity to daphnia 12.1 Eco toxicity:

and other aquatic invertebrates EC50 - Daphnia magna (Water flea) - 105 mg/1 - 24h . Cerium oxide: Toxicity to fish semi-static test EC50 - Danio rerio (zebra fish) - >200 mg/1 - 72 h. Toxicity to daphnia and other aquatic invertebrates Immobilization EC50 - Daphnia magna (Water flea) - >1000mg/1 - 48 h. Toxicity to bacteria EC50 - Sludge Treatment - >1000 mg/1 -

3 h.

12.2 Degradability: No data available.

12.3 Bioaccumulation Potential: No data available.

12.4 Mobility in Soil: No data available.

12.5 PBT & vPvB Assessment: N/A

12.6 Other Adverse Effects: N/A

Product: Xerox Phaser 4600/4620 High Revision date: 02/26/2018 Page: 6/9

13. DISPOSAL CONSIDERATIONS

Disposal Information:

Dispose as a solid waste in accordance with local authority regulations.

Empty container retains product residue.

Physical/Chemical Properties that affect Treatment:

Symbol: This product is not classified as dangerous

Risk Phrases: This product is not classified according to the federal, state and local environmental regulations.

Waste Treatment Information:

Do not shred toner cartridge, unless dust-explosion prevention measures are taken. Finely dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal, state, and local regulations.

Personal Protection Required:

N/A

14. TRANSPORT INFORMATION

14.1 ID Number: N/A

14.2 Shipping Name: N/A

14.3 Hazard Class: RID/ADR: Non-Hazardous for Transport: This substance is considered to be non-hazardous for

transport. IATA: Non-Hazardous for Air Transport. IMO: Non-Hazardous for Sea Transport.

14.4 Packing Group: N/A

14.5 Environmental Hazards: N/A

14.6 User Precautions: N/A

14.7 Bulk Transport:

15. REGULATORY INFORMATION

15.1 Regulatory Information: Regulation (EC) No. 1272/2008: Skin corrosion/irritation (Category 2). Serious eye

damage/eye irritation (Category 1). Specific target organ toxicity - single exposure

(Category 3). Specific target organ toxicity - repeated exposure (Category 2).

EPA Regulatory Information: N/A

CERCLA Reportable Quantity: N/A

15.2 Superfund Information:

Hazard Categories:

Immediate: N/A

Delayed: N/A

Fire: N/A

Pressure: N/A

Reactivity: N/A

Section 302 - Extremely Hazardous: N/A

Section 311 - Hazardous: N/A

15.3 State Regulations: N/A

15.4 Other Regulatory Information: N/A

Product: Xerox Phaser 4600/4620 High

Yield Toner Cartridge

Revision date: 02/26/2018 Page: 7/9



16. OTHER INFORMATION

General Comments:

Revision date: 02/26/2018

This information is based on our current knowledge. It should not therefore be construed as guaranteeing specific properties of the products as described or their suitability for a particular

application

Creation Date of this SDS: 02/28/2018

Product: Xerox Phaser 4600/4620 High Yield Toner Cartridge

Page: 8/9



Key to Abbreviations and Acronyms used in this sheet:

ACGIH = American Conference of Governmental Industrial	NIOSH = National Institute for Occupational Safety and Health			
Hygienists				
CERCLA = Comprehensive Environmental Response Compensati	onOSHA = Occupational Health and Safety Administration			
and Liability Act				
CLP = Classification, Labeling, and Packaging	PEL = Permissible Exposure Limit			
DSD = Dangerous Substances Directive	SCBA = Self Contained Breathing Apparatus			
EPA = Environmental Protection Agency	STOT = Specific Target Organ Toxicity			
GHS = Globally Harmonized System	TLV = Threshold Limit Value			
N/A = Not Applicable	UK = United Kingdom			
NFPA = National Fire Protection Association	UN = United Nations			

	_4	С.
к	e	Г:

DISCLAIMER

All trademarks and models referenced are property of their respective holders and are used for identification purposes only. These products are not sponsored by, affiliated with, manufactured by or distributed by the named manufacturers. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no

warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

Product: Xerox Phaser 4600/4620 High Yield Toner Cartridge

Revision date: 02/26/2018 Page: 9/9